

# **Model 2060 Specifications**

# **Dimensional Specifications:**

- 5' Reach
- 3'-4'-5' Manual Boom Extension
- 6 Lifting Height (from base of crane)
- 57" Storage Height
- 47" Overall Storage Length
- 12"x12" Mounting Space Required (for base of crane)
- 4 Bolt 9"x10" Mounting Pattern
- 3/16" X 40' Winch Cable
- 280 lbs. Operating Weight

## **Performance Specifications:**

- 6,000 ft-lb Crane Rating
- 2,000 lb Double Line Lift Capacity
- 360 degrees of continuous rotation
- with manual band brake
- -0-21-45 Degrees Boom Angle
- Winch Performance First Layer

PART LINE	LIFTING SPEED	
1	23.5 FPM	
1	21 FPM	
1	19 FPM	
1	17 FPM 57	7.34
2	7.5 FPM	
	PART LINE 1 1 1 1 2	1 23.5 FPM   1 21 FPM   1 19 FPM   1 17 FPM

### **Standard Features:**

- -12' tethered control included for operation
- Electric planetary winch.
- Powder coated components.

### **Minimum Chassis/Power Requirements**

- 8,500 lbs. GVW Rating
- 60 Amp Alternator
- 85 amp/hr Battery
- 500 Cold Cranking Amp Battery









