

D1150PXHDCU3

DUAL PRESSURE \ DUAL CAPACITY \ PORTABLE COMPRESSOR



1150CFM/350PSI 900CFM/500PSI

SPECIFICATIONS

Compressor

Model

Rated Delivery @ Rated Pressure

Operating Pressure Range Estimated Weight, Serviced Dimensions L x W x H (in")

Engine

Туре	Diesel
Make & Model	CUMMINS QSX15
Idle Speed	1400 RPM
Fuel Tank Capacity	224 gal (848 L)
Horsepower @ rated RPM	535 HP (399 kW)
Full Load Speed	1900 RPM

19,500 lbs

D1150PXHDCU3

25.5 m3/min @ 34.5 bar - 32.6 m3/min @ 24.2 bar

900 cfm @ 500 psi - 1150 cfm @ 350 psi

250 psi (17.2 bar) - 500 psi (34.5 bar)

254.31" x 90.15" x 111.82"



FEATURES

- Two Stage 20/12 Air End
- Dual Pressure 350/500 psi
- Air End Manufactured by Sullivan-Palatek, Comes With Exclusive Two Year Warranty
- Automatic 0 to 100% Capacity Control
- 8" Closed Start Inlet Valve
- 3" Service Connection
- Oil Level Sight Gauge
- Cummins Engine
- Steel Fuel Tank (TC Certified)
- Four Point Lifting Bail
- Dual Axle Running GearElectric Brakes
- Adjustable 3" Lunette Eye
- Noise Level Limited to Maximum of 76 dBA at 7 Meters
- Automatic Shutdown and Protection System
- Direct Drive
- Containment Base
- Large Service Doors for Easy Maintenance
- Automatic Blowdown Valve
 Dual Air Outlets (with Aftercooler option)

CONTROLLER

Sullivan-Palatek Electronic Controller (SPEC) Digital Readouts:

- Compressor temperature
- Discharge Pressure
- Engine oil pressure
- Engine Coolant temperature
- Voltmeter
- Tachometer
- Fuel level low fuel warning and shutdown
- Complete engine diagnostic tool
- Unit converter
- Multilingual capabilities
- Waterproof IP66/67
- Air Filter Service
- After cooler filter warning

Wenzco Supplies

191 Kelly Road Quakertown, PA 18951

800-346-7805 🛛 🌐 v

www,Wenzco.com

😤 sales@Wenzco.com